

Genuine CentriFuse®

High Performance Brake Drums



Specifications

Mtg. Type	CentriFuse Drum Part No.	Brake Size	Wt. lb.	Overall Depth	Brake Surf. Width	Hub Pilot Dia.	Bolt Circle Dia.	No. Bolt Holes	Bolt Hole Dia.	Drum Back No.	Drum Band No.	Special Information
0	90089BK	15 x 4	64	8.54	4.58	8.78	285.75	10	1.25	91294	91028	
0	91137BK	15 x 4	64	8.63	4.54	8.78	285.75	10	0.96	91136	91028	CA
0	87945BK	15 x 4	65	8.94	4.60	8.53	11.25	10	1.25	91024	91028	
0	88870BK	15 x 4	64	8.94	4.60	9.00	275	8	0.92	91025	91028	Replaces 85369, 85831, 86140, 86909
0	89870BK	15 x 4	65	8.94	4.60	8.78	285.75	10	1.25	91026	91028	
0	90660BK	15 x 4	64	8.94	4.60	8.78	285.75	10	0.96	91029	91028	
0	90174B	15 x 5	78	9.53	5.81	8.78	285.75	10	1.25	90173	87311	
0	91438B	15 x 8.62	90	11.19	9.11	9.00	275	8	0.92	91439	91480	For industry axles except Meritor TN
0	91482B	15 x 8.62	90	11.19	9.11	8.78	285.75	10	0.96	91481	91480	For industry axles except Meritor TN
0	91723B	15 x 8.62	90	11.44	9.11	9.00	275	8	0.92	91722	91480	For Meritor TN axle only
0	91725B	15 x 8.62	90	11.44	9.11	8.78	285.75	10	0.96	91724	91480	For Meritor TN or TB axle only
0	88739B	16.5 x 5	74	8.59	5.87	8.53	11.25	10	1.25	88435	87369	CA
0	90137B	16.5 x 5	74	8.59	5.87	8.78	285.75	10	1.25	91507	87369	
0	600001	16.5 x 5	75	8.88	5.46	8.78	285.75	10	1.25	90599	87369	
0	88814B	16.5 x 5	76	9.21	5.83	9.00	275	8	0.92	88810	87369	CA
0	90600B	16.5 x 5	76	9.22	5.82	8.78	285.75	10	1.25	90599	87369	0.375 thick mounting
0	600027	16.5 x 5	78	9.22	5.82	8.78	285.75	10	1.25	620020	87369	OEM specified drum
0	88507B	16.5 x 5	77	9.53	5.81	8.53	11.25	10	1.25	88508	87369	CA

Continued on Back



MADE IN USA

Notes: All CentriFuse Drums are Balanced
 I = Inboard Mounted Drum
 O = Outboard Mounted Drum
 CA = Check Availability
 CentriFuse Drum mounting face is 0.25" thick unless otherwise noted.



www.stemco.com

Safety ■ Longer Life ■ Proven Performance ■ Lightest Weight ■ Improved MPG

Specifications (cont.)

Mtg. Type	CentriFuse Drum Part No.	Brake Size	Wt. lb.	Over All Depth	Brake Surf. Width	Hub Pilot Dia.	Bolt Circle Dia.	No. Bolt Holes	Bolt Hole Dia.	Drum Back No.	Drum Band No.	Special Information
O	91265B	16.5 x 6	88	9.62	6.68	8.78	285.75	10	1.25	91264	87298	Replaces 91049B
I	87415B	16.5 x 7	85	8.66	7.64	9.50	11.25	10	0.81	87416	87105	Replaces 85130 & 86134
I	87407B	16.5 x 7	85	9.66	7.58	9.44	11.25	10	0.81	88152	87105	Replaces 85369, 85831, 86140, 86909
O	89651B	16.5 x 7	88	10.04	7.24	9.00	275	8	0.92	88798	87298	
O	87295B	16.5 x 7	88	10.04	7.27	8.53	11.25	10	0.81	91611	87298	
O	89877B	16.5 x 7	88	10.04	7.27	8.78	285.75	10	0.96	91538	87298	
O	600004HD	16.5 x 7	100	10.41	7.64	8.78	285.75	10	0.96	91538	610021	CentriFuse® HD
O	600084	16.5 x 7	83	10.41	7.64	8.78	285.75	10	0.96	91538	610001	CentriFuse® Lite
O	87101B	16.5 x 7	89	10.41	7.64	8.53	11.25	10	0.81	91611	87105	Replaces 86879
O	87156B	16.5 x 7	90	10.41	7.64	9.00	11.25	10	0.81	87157	87105	Replaces 86232
O	88797B	16.5 x 7	89	10.41	7.64	9.00	275	8	0.92	88798	87105	
O	89996B	16.5 x 7	89	10.41	7.64	8.78	285.75	10	0.96	91538	87105	
O	600013HD	16.5 x 8	104	10.91	8.55	8.78	285.75	10	0.96	91793	610023	CentriFuse® HD
O	91792B	16.5 x 8	90	10.91	8.55	8.78	285.75	10	0.96	91793	91795	
O	600014HD	16.5 x 8.62	111	11.34	9.10	8.78	285.75	10	0.96	91813	610025	0.375 thick mounting, CentriFuse® HD
O	600026	16.5 x 8.62	100	11.34	9.10	8.78	285.75	10	0.96	91813	610029	0.375 thick mounting, Replaces 91812B
O	89467B	16.5 x 8.62	95	11.89	9.10	8.53	11.25	10	0.81	91611	610029	
O	90434B	16.5 x 8.62	95	11.89	9.10	8.78	285.75	10	0.96	91538	610029	
O	89571B	16.5 x 8.62	97	12.15	9.36	9.00	275	8	0.92	88798	87618	
O	87615B	16.5 x 8.62	95	12.15	9.36	8.53	11.25	10	0.81	91611	87618	Replaces 86889
O	90486B	16.5 x 8.62	97	12.15	9.36	8.78	285.75	10	0.96	91538	87618	

Notes: All CentriFuse Drums are Balanced
 I = Inboard Mounted Drum
 O = Outboard Mounted Drum
 CA = Check Availability
 CentriFuse Drum mounting face is 0.25" thick unless otherwise noted.